

CCC 认证线 BV/BV-90

CCC Wire BV/BV-90

■ 技术参数 Specifications

额定电压(Nominal voltage): 450/750
额定温度(Temperature range): 70°C/90°C
标准(Standard): GB/T5023.3-2008/IEC60227-3:1997

■ 应用 Applications

适用于各种灯饰、家用电器、电热制品、电气设备等。
Widely used for varieties of lighting, home appliance, electrothermal products, electrical equipment etc.

导体: 裸铜
Conductor: Bare copper

绝缘体: 聚氯乙烯
Insulation: PVC

■ 印字 Marking

东莞市中为线缆科技有限公司 CCC A061837 201601010589**** 300/500V 60227 IEC 01 (BV) 1.50mm²GB/T5023.3-2008/IEC60227-3:1997

■ 规格值 Product dimensions

导体 Conductor			绝缘体 Insulation	完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
面积 Cross Section (mm ²)	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)			
(01)BV1.5mm ²	30/0.254	1.60	0.71	3.02	12.1	100/200
(01)BV2.5mm ²	50/0.254	2.06	0.82	3.70	7.41	100/200
(01)BV4.0mm ²	77/0.254	2.58	0.86	4.30	4.61	100/200
(01)BV6.0mm ²	119/0.254	3.16	0.87	4.90	3.08	100/200
(07)BV-90 1.5mm ²	30/0.254	1.60	0.71	3.02	12.1	100/200
(07)BV-90 2.5mm ²	50/0.254	2.06	0.82	3.70	7.41	100/200
(07)BV-90 4.0mm ²	77/0.254	2.58	0.86	4.30	4.61	100/200
(07)BV-90 6.0mm ²	119/0.254	3.16	0.87	4.90	3.08	100/200

■ 颜色 Colours : All colours