

CCC 认证线 BVR

CCC Wire BVR

■ 技术参数 Specifications

额定电压(Nominal voltage): 300/500

额定温度(Temperature range): 70°C/90°C

标准(Standard): GB/T5023.3-2008/IEC60227-3:1997

■ 应用 Applications

适用于各种灯饰、家用电器、电热制品、电气设备等。
Widely used for varieties of lighting, home appliance, electrothermal products, electrical equipment etc.

导体: 裸铜
Conductor: Bare copper

绝缘体: 聚氯乙烯
Insulation: PVC

■ 印字 Marking

东莞市中为线缆科技有限公司 CCC A061837 201601010589**** 300/500V 60227 IEC 01 (BV) 1.50mm² GB/T5023.3-2008/IEC60227-3:1997

■ 规格值 Product dimensions

导体 Conductor			绝缘体 Insulation	完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
面积 Cross Section (mm ²)	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)			
0.75	24/0.20	1.13	0.70	2.53	26	100/200
1.0	32/0.20	1.31	0.70	2.71	19.5	100/200
1.5	30/0.25	1.58	0.70	2.98	12.1	100/200
2.5	50/0.25	2.06	0.80	3.66	7.41	100/200
4	56/0.30	2.61	0.80	4.21	4.61	100/200
6	84/0.30	3.21	0.80	4.81	3.08	100/200
10	142/0.30	4.20	1.00	6.20	1.91	100/200
16	227/0.30	5.16	1.00	7.16	1.0	100/200
25	350/0.30	6.62	1.20	9.02	0.792	100/200
35	497/0.30	7.71	1.20	10.11	0.5	100/200
50	707/0.30	9.04	1.40	11.84	0.38	100/200

■ 颜色 Colours : All colours