

CCC 认证线 RV/RV-90

CCC Wire RV/RV-90

■ 技术参数 Specifications

额定电压(Nominal voltage): 300/500~450/750

额定温度(Temperature range): 70°C/90°C

标准(Standard): GB/T5023.3-2008/IEC60227-3:1997

■ 应用 Applications

适用于各种灯饰、家用电器、电热制品、电气设备等。
Widely used for varieties of lighting, home appliance, electrothermal products, electrical equipment etc.

导体: 裸铜
Conductor: Bare copper

绝缘体: 聚氯乙烯
Insulation: PVC

■ 印字 Marking

东莞市中为线缆科技有限公司 CCC A061837 201601010589**** 300/500V 60227 IEC 06 (RV) 0.75mm²GB/T5023.3-2008/IEC60227-3:1997

■ 规格值 Product dimensions

导体 Conductor			绝缘体 Insulation	完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
面积 Cross Section (mm ²)	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)			
(02)RV1.5mm ²	30/0.254	1.60	0.70	3.00	13.3	200
(02)RV2.5mm ²	50/0.254	2.10	0.80	3.70	7.98	200
(06)RV0.5mm ²	20/0.18	0.90	0.60	2.10	39	200
(06)RV0.75mm ²	24/0.20	1.20	0.60	2.40	26	200
(06)RV1.0mm ²	32/0.20	1.30	0.60	2.50	19.5	200
(08)RV-90 0.50mm ²	20/0.18	0.90	0.60	2.10	39	200
(08)RV-90 0.75mm ²	24/0.20	1.20	0.60	2.40	26	200
(08)RV-90 1.0mm ²	32/0.10	1.30	0.60	2.50	19.5	200
(08)RV-90 1.50mm ²	30/0.254	1.60	0.70	3.00	13.3	200
(08)RV-90 2.50mm ²	50/0.254	2.10	0.80	3.70	7.98	200

■ 颜色 Colours : All colours