

QB-B

汽车电气系统用线

Wiring for automotive electrical systems

■ 技术参数 Specifications

额定电压(Nominal voltage): 60V

额定温度(Temperature range): -40~105°C

标准(Standard): QC/T730 /ISO6722

■ 应用 Applications

汽车电气系统用线

Wires for automotive electrical systems

导体: 镀锡或裸铜
Conductor: Tinned copper
or bare copper

绝缘体: PVC
Insulation: PVC

■ 印字 Marking

QC/T25085-2010-QB-B-105°C 0.13mm²

■ 规格值 Product dimensions

导体 Conductor			绝缘体 Insulation	完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
面积 Cross Section (mm ²)	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)			
0.13	7/0.16	0.48	0.25	1.01	136	1000
0.22	7/0.20	0.60	0.25	1.13	84.4	1000
0.35	7/0.26	0.78	0.25	1.32	54.4	1000
0.35	12/0.20	0.81	0.25	1.35	54.4	1000
0.50	16/0.20	0.95	0.325	1.65	37.1	1000
0.75	24/0.20	1.16	0.30	1.81	24.7	1000
1	32/0.20	1.34	0.30	2.00	18.5	500
1.5	30/0.25	1.62	0.30	2.29	12.7	500
2	65/0.20	1.90	0.35	2.68	9.42	500
2.5	50/0.25	2.10	0.35	2.88	7.6	500
3	65/0.25	2.40	0.40	3.30	6.15	500
4	56/0.30	2.65	0.40	3.55	4.71	250
5	70/0.30	3.00	0.40	3.91	3.94	250
6	84/0.30	3.27	0.40	4.19	3.14	250
10	80/0.40	4.5	0.60	5.87	1.82	100
16	126/0.40	6.3	0.65	7.83	1.16	100
25	196/0.40	7.8	0.65	9.37	0.743	100

■ 颜色 Colours : All colours