

UL 1617


PVC双层线 PVC double-layer wire

■ 技术参数 Specifications

额定电压(Nominal voltage): 600V
额定温度(Temperature range): 105°C
标准(Standard): UL758

■ 应用 Applications

电器、电子设备内部配线
Internal wiring of electronic equipment



■ 印字 Marking

E529032  AWM 1617 18AWG 105°C 600V VW-1 PVC  AWM 1A/B 18AWG 105°C 600V FT1 ZHONGWEI

■ 规格值 Product dimensions

30AWG~2AWG

UL Style & CSA Type	导体 Conductor			绝缘体 Insulation	外被 Jacket	完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
	线规 Size (AWG)	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)	外被厚度 Jacket Thickness (mm)			
绞线 (Stranded)	28	7/0.127	0.38	0.76	0.40	2.80	138	610/2000
	26	7/0.16	0.48	0.76	0.40	2.90	138	610/2000
	24	11/0.16	0.61	0.76	0.40	3.00	85.9	610/2000
	22	17/0.16	0.77	0.76	0.40	3.20	54.3	610/2000
	20	21/0.18	0.92	0.76	0.45	3.40	33.9	610/2000
	18	34/0.18	1.19	0.76	0.45	3.60	21.4	305/1000
先绞后镀 Top-coated	24	7/0.20	0.61	0.76	0.30	2.90	85.9	610/2000
	22	7/0.254	0.77	0.76	0.30	3.00	54.3	610/2000
	20	7/0.31	0.92	0.76	0.35	3.20	33.9	610/2000
单股 Solid	24	1/0.50	0.50	0.76	0.40	2.90	85.9	610/2000
	22	1/0.64	0.64	0.76	0.40	3.10	54.3	610/2000
	20	1/0.81	0.81	0.76	0.40	3.25	33.9	610/2000
	18	1/1.02	1.02	0.76	0.45	3.50	22.2	305/1000

■ 颜色 Colours : All colours