

UL 20080

PVC排线 PVC sheathed wire

■ 技术参数 Specifications

额定电压(Nominal voltage): 30V
额定温度(Temperature range): 105°C
标准(Standard): UL758

■ 应用 Applications

音频、视频和电子设备中 2 类电路的内部布线。
Internal Wiring of Class 2 Circuits in Audio,
Video and Electronic Equipment.

导体: 镀锡铜
Conductor: Tinned copper

绝缘体: PVC
Insulation: PVC

■ 印字 Marking

E529032 AWM 20080 24AWG 105°C 30V VW-1 PVC A/B 105°C 30V FT1 ZHONGWEI

■ 规格值 Product dimensions

线规 Size (AWG)	导体 Conductor		绝缘体 Insulation		完成外径 Diameter (mm)	导体电阻 Max.cond Resistance (Ω/KM)	包装 Unit Length (M/FT)
	线数/线径 Construction (No./mm)	直径 Diameter (mm)	绝缘厚度 Nominal Thickness (mm)				
2*26	2*7/0.16	0.48	0.4		1.28*2.58	143	305/1000
2*24	2*7/0.20	0.61	0.4		1.41*2.84	89.3	305/1000
2*22	2*7/0.254	0.77	0.4		1.57*3.16	56.4	305/1000
2*20	2*21/0.18	0.92	0.4		1.72*3.46	35.2	305/1000
2*18	2*16/0.254	1.19	0.4		1.99*4.00	22.2	153/500
2*16	2*26/0.254	1.49	0.4		2.29*4.60	14	153/500
2*14	2*41/0.254	1.87	0.4		2.67*5.36	8.78	153/500

■ 颜色 Colours : All colours